



## FEATURES



- LED panel suitable for standard ceiling grid
- Aluminum body with PMMA diffuser
- Powder coated finish
- Non-dimmable flicker –free driver included
- ICF-rated and can be abutted and covered with insulation
- IP20 indoor use only
- Dimmable options: TRIAC, 1-10V, DALI
- Customized colours and IP54/IP66 versions upon request
- Five- year warranty

## TECHNICAL SPECS

Item No.	Size	Power	Lumen Output	CRI	Colour Temp	Dimmable
BNP0664	595x595	36	3600lm	>80Ra	4000K	Non-dim
BNP0665	595x595	36	3600lm	>80Ra	5000K	Non-dim
BNP0666	595x595	36	3600lm	>80Ra	6000K	Non-dim
BNP1234	1195x295	36	3600lm	>80Ra	4000K	Non-dim
BNP1235	1195x295	36	3600lm	>80Ra	5000K	Non-dim
BNP1236	1195x295	36	3600lm	>80Ra	6000K	Non-dim
BNP1264	1195x595	60	6500lm	>80Ra	4000K	Non-dim
BNP1265	1195x595	60	6500lm	>80Ra	5000K	Non-dim
BNP1266	1195x595	60	6500lm	>80Ra	6000K	Non-dim
BNP1264L	1195x595	45	4359lm	>80Ra	4000K	Non-dim