




FEATURES



- UGR<19 LED panel suitable for standard ceiling grid
- Aluminum body with PMMA diffuser
- Powder coated finish
- Non-dimmable flicker –free driver included
- ICF-rated and can be abutted and covered with insulation
- IP20 indoor use only
- Dimmable options: TRIAC, 1-10V, DALI
- Customized colours and IP54/IP66 versions upon request
- Five- year warranty

TECHNICAL SPECS

Item No.	Size(mm)	Power	Lumen Output	CRI	UGR	Colour Temp	Dimmable
BUP0664	595x595	36W	3600lm	>80Ra	<19	4000K	Non-dim
BUP0665	595x595	36W	3600lm	>80Ra	<19	5000K	Non-dim
BUP0666	595x595	36W	3600lm	>80Ra	<19	6000K	Non-dim
BUP1234	1195x295	36W	3600lm	>80Ra	<19	4000K	Non-dim
BUP1235	1195x295	36W	3600lm	>80Ra	<19	5000K	Non-dim
BUP1236	1195x295	36W	3600lm	>80Ra	<19	6000K	Non-dim
BUP1264	1195x595	60W	6500lm	>80Ra	<19	4000K	Non-dim
BUP1265	1195x595	60W	6500lm	>80Ra	<19	5000K	Non-dim
BUP1266	1195x595	60W	6500lm	>80Ra	<19	6000K	Non-dim